

NOTES

COPYRIGHT © 2021 - DYNAMIC ENGINEERING CONSULTANTS, PC - ALL RIGHTS RESERVED

NOTES

NOTES

PROVIDENCE LED DETAILS AND SPECIFICATIONS

RETENTION CAPACITY OF APPROXIMATELY 1,770 & 3,130 LBS. RESPECTFULLY. RECOMMENDED FOR AVERAGE FLOW

ENGINEERING DATA: INTERCEPTOR IS STRUCTURALLY AND HYDRAULICALLY ENGINEERED CONFORMING TO UNIFORM PLUMBING CODE.

FIELD EXCAVATION AND PREPARATION SHALL BE COMPLETED PRIOR TO DELIVERY OF INTERCEPTOR. USE DIMENSIONAL DATA AS SHOWN.

NOMINAL LIQUID CAPACITY IS 1500 GALLONS WITH GREASE& SOLIDS

RATE OF 5 GPM & INTERMITTENT FLOW RATE UP TO 13 GPM.

GREASE TRAP TO BE EPOXY COATED.

GREASE TRAP MODEL NO. GT-1500

MINIMUM EQUAL TO: PARK EQUIP. CO. (1-800-256-8041)

JOSEPH G. JAWORSKI

PROFESSIONAL ENGINEER

CONSTRUCTION **DETAILS**

05/18/2021 (V) SHOWN PROJECT No: 1423-99-006

1,500 GALLON GREASE TRAP DETAIL