

ACCESSIBLE PARKING SIGN ON BOLLARD DETAIL

- 1.) WHERE:
a. A DEPRESSIONED CIRCULATION PATH CROSSES THE CURB RAMP, FLARE SIDES SHALL BE PROVIDED AT A SLOPE NO STEEPER THAN 1:10
- 2.) CONSTRUCT DEPRESSIONED CURB FOR CURB RAMPS FLUSH TO ADJACENT PAVEMENT, GRADE FLOW LINE TO ENSURE POSITIVE DRAINAGE AND PREVENT FLOODING. FOR LEVEL TURNING SPACES BEHIND DEPRESSIONED CURB, ADJUST SLOPES TO PROVIDE POSITIVE DRAINAGE.
- 3.) CURB RAMPS MAY NOT EXTEND INTO ANY PORTION OF THE PARKING SPACE OR ADJACENT STRIPED ISLAND.
- 4.) COUNTER SLOPES OF ADJUTING GUTTERS AND PAVEMENT SHALL NOT BE STEEPER THAN 1:20 WITH A MAX. CROSS SLOPE OF 2%.
- 5.) A LEVEL LANDING AREA (MAX. SLOPE 2% IN ANY DIRECTION) SHALL BE PROVIDED AT THE TOP OF THE RAMP. THE LANDING CLEAR LENGTH SHALL BE 36" MIN AND THE WIDTH SHALL BE AS WIDE AS RAMPS.
- 6.) CURB RAMPS, PAVEMENT MARKINGS & APPLICABLE SIGNS SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE LATEST A.D.A. ACCESSIBILITY GUIDELINES.

NOTES:

1. PAVEMENT STRIPING FOR ALL ADA PARKING SPACES SHALL BE PAINTED AZURE BLUE.
2. WHERE AN ADA PARKING STALL MEETS A STANDARD PARKING STALL, AN AZURE BLUE AND WHITE PAVEMENT STRIPE SHALL BE PAINTED.
3. ALL PAVEMENT STRIPING, MARKINGS AND SIGNAGE SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE LATEST ADA ACCESSIBILITY GUIDELINES

NOTE: ALL PAVEMENT STRIPING, MARKINGS & APPLICABLE SIGNAGE SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE LATEST A.D.A. ACCESSIBILITY GUIDELINES.

NOTE: ARROWS AND WORDS CAN BE ARRANGED IN OTHER COMBINATIONS THAN THOSE ILLUSTRATED HERE TO ACHIEVE DESIRED RESULT
ALL PAINT TO BE THERMOPLASTIC.

SIGN POST DETAIL

**ACCESSIBLE PARKING SIGN W/ VAN
ACCESSIBLE SIGN**

PAINTED CROSSWALK STRIPING DETAIL

NOT TO SCALE

R5-1 SIGN DETAIL

R1-1 SIGN DETAIL

PARKING STALL STRIPING DETAIL
NOT TO SCALE

GENERAL NOTES:

1. FOOTING TO BE N.J.D.O.T. CLASS "C" CONCRETE.
2. INVERT & WALLS TO BE N.J.D.O.T. CLASS "C" CONCRETE.
3. IF WALL CONSTRUCTION IS OTHER THAN CONCRETE, WALLS SHALL BE PLASTERED INSIDE & OUTSIDE WITH 1/2" THICK CEMENT PLASTER.
4. FRAME & GRATE TO BE CAMPBELL FOUNDARY CO., NO. 31944 (FOR STANDARD DUTY) OR EQUIV. SET IN CONCRETE.
5. PROVIDE 3/4" ALUM. LADDER RUNGS SET AT 12" O.C.
6. WHEN ADDITIONAL DEPTH IS SCHEDULED, WALLS BELOW 8'-0" MEASURED FROM GRATE TO INVERT SHALL BE 12" THICK AND EXTEND 12" BEYOND OUTSIDE OF WALL.

6" MIN CRUSHED
STONE BEDDING UNDER
ENTIRE INLET (TYP.)

5°

2'-6"

SECTION B-B
"TERMINAL" INLET DETAIL

NOTES:

1. MATERIAL: GRAY CAST IRON ASTM A 48-83, CLASS 30B;
2. IN RETROFIT SITUATIONS, THIS CURB PIECE (HEAD) WILL FIT EXISTING CAMPBELL FOUNDRY CO. MANUFACTURED CURB INLETS FOR NUDOT TYPES B, B-1, B-2, D, D-1 AND D-2;
3. NAMEPLATE MESSAGE CAN BE MODIFIED TO YOUR SPECIFIC NEEDS WITHIN AREA SHOWN;
4. CASTING SUPPLIED WITHOUT SURFACE COATING

[illegible]

REV.	DATE	COMMENTS	BY
1	07/29/21	REVISED PER SCD & COUNTY COMMENTS	GL
2	09/10/21	REVISED PER SCD & COUNTY COMMENTS	MS
3	11/20/21	REVISED PER UPDATED DRAFT	MS
4	07/07/22	REVISED PER SCD COMMENTS	JD
5	03/15/23	NEW PER PER BOROUGH COMMENTS	JD
6	05/02/22	REVISED PER BOROUGH & SCD COMMENTS	GL
7	06/19/22	REVISED PER COUNTY COMMENTS	GL
8	07/11/22	REVISED PER BOROUGH COMMENTS	GL
9	06/30/22	REVISED PER BOROUGH COMMENTS	JD

THIS PLAN SET IS FOR PERMITTING PURPOSES
ONLY AND MAY NOT BE USED FOR CONSTRUCTION

DOWN BY:	DESIGNED BY:	CHECKED BY:	CHECKED BY:
JD	JD	DTS	-

PROJECT: **CSH OLD TAPPAN, LLC**
PROPOSED ASSISTED LIVING FACILITY
BLOCK 1606, LOT 3
244 OLD TAPPAN ROAD
BOROUGH OF OLD TAPPAN, BERGEN COUNTY, NEW JERSEY